




# Elo Touchsystems

## 1725L / 1727L



### Specifications

<b>Model</b>	1725L / 1727L
<b>Series</b>	3000
<b>Availability</b>	Worldwide
<b>Case/Bezel color</b>	1725L Dark grey 1727L Beige
<b>Display</b>	<b>Size:</b> 17.0" diagonal <b>Type:</b> Active matrix TFT LCD
<b>Useful screen area</b>	<b>Horizontal:</b> 13.3" (338 mm) <b>Vertical:</b> 10.6" (270 mm)
<b>Monitor dimensions</b>	<b>Width:</b> 17.1" (434 mm) <b>Height (inc. base):</b> 16.9" (430 mm) <b>Depth (inc. base):</b> 9.4" (238 mm)
<b>Optimal (native) resolution</b>	1280 x 1024
<b>Other supported resolutions</b>	1024 x 768 at 60, 70, or 75 Hz 832 x 624 at 75 Hz (Mac) 800 x 600 at 56, 60, 72, or 75 Hz 720 x 400 at 70 Hz 640 x 480 at 60, 72, or 75 Hz 640 x 480 at 66 Hz (Mac)
<b>Colors</b>	16.7 million with dithering, 6 bits per color data
<b>Brightness</b> LCD panel	250 cd/m <sup>2</sup> typical
<b>Brightness</b> LCD panel with touchscreen	<b>AccuTouch:</b> 205 cd/m <sup>2</sup> typical <b>IntelliTouch:</b> 230 cd/m <sup>2</sup> typical
<b>Response time</b>	16 msec (typical)
<b>Viewing angle</b> (from center)	<b>Horizontal (left/right):</b> ±80° or 160° total (typical) @ CR=5 <b>Vertical (up/down):</b> ±80° or 160° total (typical) @ CR=5
<b>Contrast ratio</b>	450:1 (typical)
<b>Input video format</b>	Analog (no proprietary video card needed); Digital Video Input (DVI-D)
<b>Input video signal connector</b>	Mini D-Sub 15-Pin; DVI-D
<b>Input frequency</b>	<b>Horizontal:</b> 31.5–80 kHz <b>Vertical:</b> 56–75 Hz
<b>Power supply</b>	External power supply, 100–240 VAC, 50–60 Hz <b>Monitor input voltage:</b> 19V <b>Current:</b> 3.42A
<b>Power dissipation</b>	45 W max.

<b>Temperature</b>	<b>Operating:</b> 0°C to 40°C <b>Storage:</b> -20°C to 60°C
<b>Humidity</b>	<b>Operating:</b> 20%–80% <b>Storage:</b> 5%–95% noncondensing
<b>Weight</b> (approx.)	<b>Actual:</b> 21.6 lb (9.82 kg) <b>Shipping:</b> 30.6 lb (13.9 kg)
<b>Warranty</b>	<b>Monitor:</b> 3 years <b>Touch technology:</b> 5 years AccuTouch, 10 years IntelliTouch <b>Backlight lamp life:</b> typical 40,000 hours to half brightness
<b>Agency approvals</b>	UL, cUL, FCC, IC, CE, TÜV-GS, VCCI, C-Tick
<b>Speakers</b>	Two built-in, rear-facing 1W speakers in display head
<b>On-screen display (OSD)</b>	OSD lockouts for power and user controls OSD extras include volume, treble, bass, balance
<b>User's controls</b>	<b>Side:</b> auto, enter, ±, menu, power <b>OSD:</b> contrast, brightness, H/V position, color, temperature, clock, phase, recall, OSD time, language (English, German, Spanish, Japanese, French) <b>OSD disable/enable:</b> power, volume, and/or OSD menu
<b>Mounting options</b>	100 mm or 75 mm M4 <a href="#">VESA mount</a> 100 mm M5 threaded holes on base bottom for table top security Removable base Reversible stand for wall mounting Stand rotates from -5° (from vertical) to 90° (horizontal)



**computermiete.de**

Dieses Produkt können Sie mieten bei  
 computermiete.de  
 Tel. +49 - (0)721-93244-10  
 E-Mail: juergen.wagner@computermiete.de